

SPI ETIQUETAGE

EZ-Direct Thermal Printer

EZ Options



Easy Label Holder



Simple to maintain



Useful Interface



Wall-mounted Feature



EZ DT
series



SPI Etiquetage - 14, rue du Carlier 16800 Soyaux - Tél : 0545/95/8451
Fax : 0545/95/8108 - Mail : spi.eti@wanadoo.fr -
Site Internet : www.spi-etiquetage.fr

EZ-DT series Product Specifications

Model	EZ-DT-4	EZ-DT-2
Resolution	203 dpi (8 dot/mm)	
Print Mode	Direct Thermal	
CPU	32 Bit	
Memory	4MB Flash, 8MB SDRAM (with RTC)	4MB Flash, 8MB SDRAM
Print Speed	2 IPS – 4 IPS	
Print Length	Min 12.7 mm (0.5") Max 1727 mm (68")	
Print Width	Max 198 mm (7.83")	Max 94 mm (3.7")
Sensor Type	Adjustable Reflective sensor, Fixed transmissive, center aligned.	
Sensor Detection	Type : Label gap and black mark sensing Detection : Label length auto sensing and / or program command setting	
Media	Label Roll : Max. 127 mm (5") Core Diameter : 1", 1.5" Width : 25 mm (1") – 118 mm (4.64") Thickness : 0.08 mm – 0.20 mm (0.0025" – 0.0079")	Label Roll : Max. 127 mm (5") Core Diameter : 1", 1.5" Width : 25 mm (1") – 118 mm (4.64") Thickness : 0.08 mm – 0.20 mm (0.0025" – 0.0079")
Printer Language	EZPL (Firmware downloadable)	
Software	Application : QLabel-IV (EZPL only) DLL & Driver : Microsoft Windows NT 4.0, 2000, XP and Vista	
Resident Fonts	11 resident alphanumeric fonts (included OCR A & B) ; those are expandable 8 times horizontally and vertically. All bit mapped fonts in 8 orientations. Scalable Font (Code Page 800 & 852) in 4 orientations.	
Fonts Download	Windows bit mapped in 8 orientations. True Type font (Ver. 2.XX) and Asian fonts in 4 orientations.	
Image Handling	BMP, PCX, Support ICO, WMF, JPG, EMF file through software	
Barcodes	Code 39, Code 93, Code 128 (subset A, B, C) ; UCC/EAN-128 K-Mat, UCC/EAN-128, UPC A / E (add on 2 & 5) ; 12 of 5, 12 of 6 with Shipping Bearer Bars, EAN 8 / 13 (add on 2 & 5) ; Codabar, Post NET, EAN 128, DUN 14, MaxiCode, HIBC, Plassey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF417, Datamatrix code & QR code	
Interfaces	Serial port : RS-232 (Baud rate : 4800 – 115200, Xon/Xoff, DSR/DTR) USB port : V2.0	Serial port : RS-232 (Baud rate : 4800 – 115200, Xon/Xoff, DSR/DTR) USB port : V2.0
Control Panel	One Tri-color LED : Power (Red, Orange and Green) Function Key : FEED	
Power	Auto Switching 100/240VAC, 50/60 Hz	
Environment	Operation : 41°F to 104°F (5°C to 40°C) Storage : -4°F to 122°F (-20°C to 50°C)	
Humidity	Operation : 30-85%, non-condensing, Free air Storage : 10-90%, non-condensing, Free air	
Cert. Approval	CE, FCC Class A, CCC, CB, cUL, BSMI	
Printer Dimension	Length : 218 mm (8.58") Height : 186 mm (7.32") Width : 168 mm (6.61") Weight : 1.3 Kg	Length : 218 mm (8.58") Height : 172 mm (6.77") Width : 100 mm (3.94") Weight : 1.2 Kg
Options	Guillotine Cutter Module Stripper Module Internal Ethernet Adapter Card	Guillotine Cutter Module Stripper Module Internal Ethernet Adapter Card
Packing	USB cable, Power cord, CD, Quick Start Guide, Cleaning card.	

Specifications are subject to change without notice.